



DESCRIPTION

Chemguard LM2000 is an acrylic based with good resistance to penetration of oil and liquid, chemguard LM2000 is designed to use in warehouse, garage, light industrial building and car parks which can provide demarcation and numbering of car parking bays. It is also used to assist traffic management by providing directional arrows and hatching.

AVANTAGE

- UV Resistance
- Can be applied over freshly placed concrete
- Durable finish
- Dust Proof
- Quick dry properties
- Easy to apply

SURFACE PREPARATION

Clean and mechanically abrade. All residues must be removed to provide a dry, dust free open textured surface.

MIXING

Power mix to achieve homogeneous appearance. Avoid excessive air entrapment.

APPLICATION

Apply using brush, ruler or compressed air.

DRYING TIME

Top coat	2 hours
Full cure	6 hours

TECHNICAL INFORMATION

Color	Available in wide range, Consult Unichem Technical Department.
Solid content	30% ± 2% by Volume
Specific Gravity	1.03 ± 0.02

APPLICATION CONDITIONS

Min. Temperature 7°C

THEORETICAL COVERAGE

The coverage rate is around 6 m²/L, depending in surface porosity.

SHELF LIFE

12 months when stored properly in unopened container in dry conditions at 10 - 25°C.

CLEANUP

Tools and equipment can be cleaned by thinner #10.

PACKAGING

Chemguard LM2000 LINEMARKER is available in 5 Liter or 25 Liter.

PRECAUTIONS

Avoid applying under direct sunlight, KEEP OUT OF REACH OF CHILDREN. Use with adequate ventilation and use a respirator when levels are above applicable limits.

Avoid contact with skin and eyes. Close container after each use. Use good hygiene when handling this product.

TECHNICAL SUPPORT

Technical assistance is available from the manufacturers trained field representatives.

UPDATED

December 2012

1976

Protective Coatings . Linings . Fire Proofing . Floorings . Construction Chemicals & Decorative Paints

Unichem Product Group

Unichem offers a wide range of industrial coatings, fireproofing and construction chemicals products that are manufactured, which include:

Intumescent coatings

Fire retardants

Industrial floorings.

Steel and industrial coatings

Waterproofing.

Grouts and anchoring

Concrete repairs.

Structural protection.

United Chemical Company

P.O. Box 3458, Amman 11181, Jordan

Tel. +962 6 420 3366, Fax. +962 6 420 3368

info@unichemgroup.com, www.unichemgroup.com

