



**DESCRIPTION**

A ready to use resurfacing putty filler intended for patching, repairing, and or resurfacing internal building surfaces.

It is based on an alkali - resistant synthetic binder and fortified with inert fillers for use on all common types of building surfaces, to give a high quality smooth surface.

**RECOMMENDED USE**

For the resurfacing of irregularities in cement and gypsum based substrates.

**SURFACE PREPARATION**

Surfaces must be clean and sound. Employ adequate methods to remove dirt, dust, oil and all other contaminants that could interfere with adhesion.

Surfaces must be primed with appropriate primer such as Novaseal Primer or other.

**MIXING**

Product is ready for use. Mix softly with trowel or spatula before application.

**THINNING**

Not Recommended

**APPLICATION**

Apply by trowel or spatula. If more than one coat is required, for best results sand lightly, prime in between coats, and allow overnight to dry.

**DRYING TIME**

Touch dry surface	1 hour
Top coat	24 hours
Full cure	7 days at 24°C and 50% RH

**TECHNICAL INFORMATION**

Color	White
Specific gravity	1.71 g/cm <sup>3</sup> ± 0.02
Solids by volume	70% ± 2%
Dry Film Thickness	100 μ

**APPLICATION CONDITIONS**

Min. Temperature	5°C
Max. Temperature	39°C
Relative Humidity	85%

**THEORETICAL COVERAGE**

The coverage rate is around 7 m<sup>2</sup>/L at 100μ thickness

**SHELF LIFE**

12 months when stored properly in unopened container in dry conditions at 10 - 25°C.

**CLEANUP**

Tools and equipment can be cleaned with Clean with water

**PACKAGING**

PLASTRO is available in 5 Kg and 25 Kg Bag.

**PRECAUTIONS**

KEEP OUT OF REACH OF CHILDREN. Use with adequate ventilation and use a respirator when levels are above applicable limits.

Avoid contact with skin and eyes. Close container after each use. Use good hygiene when handling this product

**TECHNICAL SUPPORT**

Technical assistance is available from the manufacturers trained field representatives.

**UPDATED**

December 2012

1976

Protective Coatings . Linings . Fire Proofing . Floorings . Construction Chemicals & Decorative Paints

### **Unichem Product Group**

Unichem offers a wide range of industrial coatings, fireproofing and construction chemicals products that are manufactured, which include:

Intumescent coatings

Fire retardants

Industrial floorings.

Steel and industrial coatings

Waterproofing.

Grouts and anchoring

Concrete repairs.

Structural protection.

---

**United Chemical Company**

P.O. Box 3458, Amman 11181, Jordan

Tel. +962 6 420 3366, Fax. +962 6 420 3368

[info@unichemgroup.com](mailto:info@unichemgroup.com), [www.unichemgroup.com](http://www.unichemgroup.com)

