



DESCRIPTION

A heavy duty, external quality textured coating formulated with special pure acrylic resin. Specially designed to give a uniform flexible protective and decorative textured finish. It disguises surface irregularities and defects, bridges hair cracks and surface voids. It is highly durable, economical and easy to apply. Available in fine and coarse textures.

RECOMMENDED USE

Recommended for application over a wide variety of surfaces. Particularly suitable for use over cement plaster, dry walls, masonry surfaces, stucco, concrete blocks, brick, gypsum board, cement asbestos board, and even on properly primed wooden substrates.

SURFACE PREPARATION

Surfaces must be clean and sound. Employ adequate methods to remove dirt, dust, oil and all other contaminants that could interfere with adhesion.

Allow surfaces to cure sufficiently before application of paint system.

MIXING

Power mix to achieve homogeneous appearance. Avoid excessive air entrapment.

THINNING

Not required. May be thinned with potable water for spray application (Consult UNICHEM Technical Support Department for specific recommendations).

APPLICATION

All surfaces should be dry, clean, and free from oil, grease, dirt and other contamination. Previously painted surfaces should be thoroughly cleaned, and all loose paint and other materials, detrimental to paint adhesion should be removed by sanding and then dust cleaning. Prime surface with UNICHEM / Novaseal® Latex Primer

Sealer Apply by roller. Can also be spray applied (consult UNICHEM Technical Support Department for instructions). Large cracks and holes should be filled with the proper patching compound.

DRYING TIME

Touch dry surface 3 hours

Top coat 5 hours at 24°C

TECHNICAL INFORMATION

Color	Wide range
Viscosity	Pasty
Solids by weight	72% ± 2
Solids by volume	58% ± 2
Density	1.46Kg/L

APPLICATION CONDITIONS

Min. Temperature 5°C

Max. Temperature 39°C

Relative Humidity 89%

THEORETICAL COVERAGE

Coverage depends upon surface texture and porosity, as well on application technique (ranges between 2m² / Gallon for rough texture to 6 m² / Gallon for fine texture).

SHELF LIFE

12 months when stored properly in unopened container in dry conditions at 10 - 25°C.

CLEANUP

Use a damp cloth (water) to wipe up drips and spatters promptly before paint dries. Wash equipment with warm soapy water immediately after use.

PACKAGING

Uniflex is available in 3.6L Gallon or 18L Pail.

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. Use with adequate ventilation and use a respirator when levels are above applicable limits.

Avoid contact with skin and eyes. Close container after each use. Use good hygiene when handling this product

TECHNICAL SUPPORT

Technical assistance is available from the manufacturers trained field representatives.

UPDATED

December 2012

1976

Protective Coatings . Linings . Fire Proofing . Floorings . Construction Chemicals & Decorative Paints

Unichem Product Group

Unichem offers a wide range of industrial coatings, fireproofing and construction chemicals products that are manufactured, which include:

Intumescent coatings

Fire retardants

Industrial floorings.

Steel and industrial coatings

Waterproofing.

Grouts and anchoring

Concrete repairs.

Structural protection.

United Chemical Company

P.O. Box 3458, Amman 11181, Jordan

Tel. +962 6 420 3366, Fax. +962 6 420 3368

info@unichemgroup.com, www.unichemgroup.com

